

### FEATURE

- .고강도 알루미늄 소재로서 산업용 및 상업용 전자저울에 사용
- .가격이 저렴하며 고정밀도
- .가벼운 무게를 측정하는데 있어서 편리함

### SPECIFICATION

MODEL	CBCL
Rated capacity (R.C.)	6, 10, 15, 20, 30 kgf
Rated output (R.O.)	2.0 ± 0.2 mV/V
Zero balance	0 ± 0.1 mV/V
Combined error	0.03% R.O.
Repeatability	0.01% R.O.
Creep for 30 min	0.03% R.O.
Temp. effect on zero value	0.028% / 10°C
Temp. effect on output value	0.014% / 10°C
Excitation recommended	10V DC
Excitation maximum	15V DC
Terminal resistance, input	400 ± 20Ω
Terminal resistance, output	350 ± 3.5Ω
Insulation resistance	> 2000MΩ @50V DC
Compensated temperature range	-10 to +40°C
Operating temperature range	-20 to +80°C



- Mounting  
Socket-head cap screw M6 x 1.0(10.9)  
Tightening torque : 14Nm
- Maximum Platform Size  
300 x 300mm
- Material  
Anodized Aluminum
- Cable  
Braided shield 4-wire round cable  
with PVC-jacket

### DIMENSION (mm)

